

E I DUPONT DE NEMOURS & CO INC

DUPONT POLYMERS, ENGINEERING POLYMERS NYLON RESINS PO BOX 80713,
CHESTNUT RUN PLAZA WILMINGTON DE 19880

Material Designation: 101(f1)+, 101F(f1)+, 101L(f1)+, E101(f1)+, E101L(f1), 132F(f1)+, 133L(f1)+, 135F(f1)+

Product Description: Polyamide 66 (PA66), designated "Zytel" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.71	V-2	4	0	130	75	85	725	960
	1.5	V-2	3	0	130	75	85	750	850
	3.0	V-2	2	0	130	75	85	800	950
	6.0	V-2	2	0	130	75	85	-	-
CTI: 0			HVTR: 0		D495: 6		IEC BP: -		

(f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

+ Virgin and Regrind from 1% to 50% by weight inclusive, have the same basic material characteristics.

f1 Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

NOTE (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" or "MIN".

Report Date: 07/29/1996

Underwriters Laboratories Inc®

324299147

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.