


HB split hoods with double latch bolts

For EPIC® HB 16 & HB 24 housings



Split hoods allow three or four cable assemblies to pass through one hood, providing a convenient way to pass finished cables into a panel without having to re-terminate the assembly. A maximum of four cables ranging in size from 3 mm to 16 mm each may pass through a single hood.

Both the HBSH 16 and HBSH 24 hoods can accommodate any combination of the grommets listed below. When used with the grommets, the split hood provides an IP54 environmental seal.

Part number	Gland openings	Cable outer diameter	EPIC® HB panel mount base
HBSH16	3 openings	3 mm - 16 mm	100720C0
HBSH24	4 openings	3 mm - 16 mm	101020C0

Split hood grommets



Thermoplastic rubber split grommets are available in a range of sizes. The grommets seal around the cables and provide IP54 protection as well as strain relief in the mated and assembled position. The HBSH 16 housing is capable of accommodating 3 glands; the HBSH 24 housing can accommodate 4 glands.

Technical data	
Material:	thermoplastic rubber (UL approved)
Temperature range:	-40°C to +140°C

Part number	Clamp range mm	Pack size
SHG 3	3 - 4	10
SHG 4	4 - 5	10
SHG 5	5 - 6	10
SHG 6	6 - 7	10
SHG 7	7 - 8	10
SHG 8	8 - 9	10
SHG 9	9 - 10	10

Part number	Clamp range mm	Pack size
SHG10	10 - 11	10
SHG11	11 - 12	10
SHG12	12 - 13	10
SHG13	13 - 14	10
SHG14	14 - 15	10
SHG15	15 - 16	10
SHG 0	blank	10

If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question.