



RECOMMENDED  
PANEL CUT-OUT

② Notes:

1. Waterproof connector rating is IP67/IP68
2. Insulation Resistance: >100MΩ
3. Contact Resistance of connector: ≤10mΩ
4. Mating Cycle: 100 times Min, 500 times Max.
5. Operating temperature: -25°C ~ +85°C
- ⑥. Unshielded

ITEM	SPECIFICATION	QTY	UNIT
△	BLACK GLUE AB (ETHOXYLINE RESIN)	2	G
△	O-RING GREEN FKM Ø13.0 * Ø2.0mm	1	PCS
△	PG9 BRASS PLATED NI L*W=2.8*18mm	1	PCS
△	M12 BRASS WITH NI PLATED, FRONT MOUNT PG9 L=21.0mm	1	PCS
① △	M12 FEMALE Connector UL94V-0 Black Solder Pin 1u" Gold plated	1	SET

**RoHS compliant**  
Unit: mm

Scale	Free	Date	Name
<b>TOLERANCE</b>			
.X	±0.5	06.09.2019	Any
.XX	±0.20	17.07.2018	Segal
<b>DIM TOL</b>			
X.°	±2.0°	26.04.2019	Segal
.X°	±1.0°	17.07.2018	Segal
Angle	TOL		

Customer-No.	Customer-No.
ASSMANN WSW-No. A-M12-xx-FGMX-GHB3a	ASSMANN WSW-No. A-M12-05-FGMB-GHB3a

1 2 3 4 5 6 7



ASS 8057 CO

rev02

Replace

Sheet